



A compact valve box with 4 internal solenoid valves that connect to either a 24Vac or 9Vdc Latching irrigation controller. Installation is uncomplicated and the eZyvalve®4 provides a trouble free way to distribute water to a micro irrigation system.

### Features

- Pre-assembled with no internal pipe connections.
- High strength UV stabilised materials.
- Includes cable seal and wire connectors.
- Water, dust and pest resistant.
- Textured non-slip lid with o-ring seal and stainless steel screws.
- 3/4" BSP male threaded inlet and outlet connections.

### Applications

Landscape, home gardens, greenhouses and nurseries. Above and below ground installation.



eZyvalve®4 - 24Vac



eZyvalve®4 - 9Vdc Latch



Braided Hose



eZyvalve®4 with Braided Hose

Performance	
FLOW RATE (lpm)	PRESSURE LOSS (kPa)
10	30
15	63
20	108
25	165
30	231

### eZyvalve®4

TYPE	ORDER CODE	PACK QUANTITY	PACKS PER CARTON	CARTON (kg)
eZyvalve®4 - Valve Box 4 Solenoid Valves 3/4" BSPM 24Vac	<b>16605</b>	1	10	11.5
eZyvalve®4 - Valve Box 4 Solenoid Valves 3/4" BSPM 9Vdc Latch	<b>16625</b>	1	10	12.1

### Accessories

TYPE	ORDER CODE	PACK QUANTITY	PACKS PER CARTON	CARTON (kg)
BRAIDED HOSE 1000 mm x 3/4" BSPF	<b>90603</b>	1	40	16.1
TAP ADAPTOR 1" BSPF x 3/4" BSPM	<b>45825</b>	25	30	12.0

### Specifications

DIMENSIONS PACKAGED		CONNECTION TYPE	
LENGTH	105 mm	Inlet:	3/4" BSPM tapered
DEPTH	182 mm	Outlet:	3/4" BSPM parallel x 4
WIDTH	182 mm		
WEIGHT (approx) - 24Vac	1075 g		
WEIGHT (approx) - 9Vdc Latch	1150 g		

OPERATING SPECIFICATIONS	
FLOW	1 L/min - 30 L/min
PRESSURE - 24Vac	20 kPa - 1250 kPa
PRESSURE - 9Vdc	20 kPa - 750 kPa
AMBIENT TEMPERATURE	2°C - 60°C
ELECTRICAL - 24Vac	24Vac, inrush current 320 mA, holding current 260 mA at 50 Hz
ELECTRICAL - 9Vdc Latch	9Vdc, inrush current 1200 mA